



Elastadeck Matting

SS6000829

intended uses

For the reinforcement of Elastadeck Balcony waterproofing systems.

The random nature of the weave allows the fibres to be easily incorporated within the balcony coating and be moulded easily to rough and irregular surfaces. When encapsulated, the fibres help provide greater tensile strength and tear resistance to the balcony system.

product description

Random weave chopped strand glass fibre mat (nominal 100g/m²)

product information

Product reference	SS6000116
--------------------------	-----------

Colour	Natural
---------------	---------

storage and handling

Storage	Store in original packaging in a dry safe place out of the reach of children. Avoid frequent handling (wear gloves for direct contact). Glass fibres are not classified as dangerous with regard to transport regulations and are not required to follow special procedures.
----------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Pack Size	Nominal 0.85m wide x 50m long (the exact length may slightly vary from roll to roll).
------------------	---------------------------------------------------------------------------------------

Flash point	Non flammable
--------------------	---------------

Product weight	Nominal gross wt. per 100m roll circa.4.5kg
-----------------------	---------------------------------------------

Shelf life	Unlimited if stored in unopened packages as above.
-------------------	----------------------------------------------------

preparation and application

Apply Elastadeck Grit Coat, whilst wet insert Elastadeck Matting and thoroughly "wet-in".

Overlap adjacent reinforcement areas already laid by at least 50mm ensuring sufficient extra embedment material is applied to these areas.

When embedding Elastadeck Matting it may be necessary to tamp the mat. If so, use a short bristled brush or specialist roller ensuring that there are no tented areas. Immediately after embedding check for any upstanding glass fibre strands and lay smooth.

safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.

Minimum precautions:

1. Avoid skin and eye contact i.e. wear gloves, goggles, long sleeve clothing to avoid temporary irritation.
2. Keep away from food, drink, animal foodstuffs, plants or fish.
3. Do not eat or smoke in the vicinity of work.
4. Dispose of empty container in a safe way.
5. Wash hands before eating.

disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

SS6000829

Updated: December 2019