

# Elastaseal™ Z Accelerator Solution

RC143

## intended uses

For use in conjunction with 12.5 litre units of RC140/RC141/RC142 to accelerate cure and enable faster return to service of the roof.

## product description

A single pack coloured, solvent thin additive.

## product information

<b>Product reference</b>	RC113
<b>Volume solids</b>	55%
<b>Typical thickness</b>	N/A
<b>Theoretical coverage</b>	N/A
<b>Practical coverage</b>	N/A
<b>Appearance/Colour range</b>	Blue/green translucent liquid
<b>VOC content</b>	Max approx 450g/litre. (Cat A/i), EU limit N/A

## application details

<b>Mix ratio</b>	250g unit to be added to RC140/RC141/RC142 Shake well before use.
<b>Method of application</b>	N/A

<b>Cleaner</b>	Elastaseal Z Cleaning Solvent
----------------	-------------------------------

<b>Pot Life</b>	N/A
-----------------	-----

<b>Drying time</b>	Mixed into Elastaseal Z Embedment Coat (RC140)
--------------------	--

Substrate Temperature	Touch Dry	Hard Dry	Overcoating Interval	
			Minimum	Maximum
20°C no accelerator	8hrs	Overnight	Overnight	7days
20°C accelerated	2hrs	3hrs	3hrs	7days
5°C no accelerator	Overnight	2-3days	2-3days	7days
5°C accelerated	4-6hrs	Overnight	Overnight	7days

**Note:** Drying/curing times will be shortened by higher temperatures and lengthened by lower temperatures

## storage and handling

<b>Storage</b>	Store the closed containers in a store room away from sources of ignition.
<b>Pack Size</b>	250 grams
<b>Flash point</b>	102°C (approx)
<b>Shelf life</b>	12 months from manufacturing date in unopened containers

## surface preparation

Ensure all surfaces are clean, sound, dry and free from oil, grease, grime and other surface contaminants.

## limitations

This product should only be used by Tor Coatings Approved Contractors (further details on request).

Overcoating must be carried out within the timescale overleaf otherwise further preparation will be necessary.

## safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.

Minimum precautions for all paints:

1. Avoid skin and eye contact i.e. wear gloves, goggles, etc
2. Ensure good ventilation, mechanical if necessary.
3. Store and use away from heat and flame.
4. Do not eat or smoke in the vicinity of work.
5. Wash hands before eating.
6. Refer to supply container for additional warning labels.

## definitions

### Tolerances

All information quoted in this data sheet is subject to normal manufacturing tolerances.

### Practical coverage

Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

### Pot Life

Applies only to two component products and refers to the time the mixture remains usable.

## disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.